

**ORLEN OIL RIDER V-TWIN 4T 20W-40****Product description and application**

High-quality engine oil for use in motorcycles, scooters and other vehicles with four-stroke engines of small capacity. It provides full protection of the lubricated parts.

**Characteristics**

- Proper protection of the engine, gearbox and clutch in motorcycles, scooters and two-wheel vehicles of another type in the full range of operating conditions
- Maintaining cleanliness of the lubricated parts
- Achieving the maximum performance of the lubricated vehicles
- Easy start-up at low ambient temperatures
- Reliability of the lubricated vehicles in a wide range of weather conditions

**Specifications and Approvals**

- SAE 20W-40
- API SL
- JASO MA2

**Typical parameters**

Requirements	Test methods according to	Unit	Value
kinematic viscosity at 100°C	ASTM D 445	mm <sup>2</sup> /s	14.0 - 16.3
pour point, not higher than	ASTM D 97	°C	-27
flashpoint, not lower than	ASTM D 92	°C	200
viscosity index, not less than	ASTM D 2270		120
structural viscosity CCS at -15°C, not higher than	ASTM D 5293	mPa*s	9500
sulphated ash content, not more than	ASTM D874	% (m/m)	1.2
The above figures are typical of those obtained with normal production batch, they are not a technical specification, due to continuous development of the product, they may change.			